

3M Science.
Applied to Life.™

3M™ VHB™ Tapes

Who says it has
to be done in the
same old way?



Every day engineers and managers like you are discovering that 3M VHB tapes are beyond strong. When used in place of mechanical fasteners, they can help you do things you never thought possible.

3M Industrial Adhesives and Tapes

3M™ VHB™ Tape

Bonding product parts with precision, ease, reliability, and strength requires an approach that breaks the barriers of traditional construction elements. 3M VHB Tapes open up a world of possibilities eliminating rivets, screws, bolts, and welds and improving design construction, aesthetics and productivity. With unmatched strength, these tapes increase the overall durability and reliability of every product bond.

Experience the strength and reliability of 3M VHB Tapes.



Invisible bond

Enhance your design appearance with virtually invisible bonding – a game-changing approach for your design concepts. Explore new possibilities and use new, innovative materials to improve the look of your products while optimising performance, preventing bi-metallic corrosion and streamlining your production processes.



A durable difference

With a bond that's built to withstand the rigours of exposure, 3M VHB Tapes resist hot, cold and cycling temperatures, UV light, moisture, and solvents. They seal against environmental conditions and damp vibration to reduce metallic wear-and-tear.



Demanding strength

For your most demanding bonding applications, 3M VHB Tapes distribute dynamic or static stress over the entire surface of the design, improving holding strength and eliminating the need for mechanical fasteners.



Application efficiency

3M VHB Tapes are simple and easy to apply, saving you time and money. The tapes bond on contact, assemble easily and can be cut to precise shapes and sizes for custom applications.



3M VHB Tape has been providing customer bonding solutions since 1980

Applications, Innovations and unlimited design possibilities.

The proven, high strength alternative to mechanical fasteners

3M VHB tapes offer manufacturers a distinct bonding advantage by spreading stress loads across the entire length of the joint, permanently adhering materials with a powerful bond.

It's time to replace screws, rivets, welds and other traditional fasteners with a better solution – 3M VHB Tape.

Panel to Frame

Solve dynamic force challenges while reducing weight and producing a clean, sharp look.



Stiffener to Panel

Experience the freedom to create unique designs with exceptional vibration and corrosion resistance.



Lens Window to Housing

Apply a secure seal to dissimilar materials, while enhancing productivity and design innovation.



More Applications

Mobile devices, signs, architectural windows, vehicles and trailers, all of these rely on 3M VHB tape for one or more steps in the assembly, mounting, fastening and sealing process.

Expertise and Support

Our application experts are here to consult with your team to determine the correct 3M VHB tapes for your product design and production process.

Our deep expertise in bonding dissimilar materials for challenging applications is unmatched. 3M stands alone in its capabilities, facilities and experience. Leverage our expertise to your competitive advantage.

Selecting the right 3M VHB Tape for your application is easy.

Online selector

Try our new selector to find the right 3M VHB product for your bonding needs
<http://go.3M.com/tapeselector>

Call us

You can discuss your application and have your questions answered with one of our industrial representatives by calling 0870 60 800 50

Visit our website

For further information visit
www.3M.co.uk/VHB

3M™ VHB™ Industrial Adhesives and Tapes	Products									
	Product code	Thickness (mm)	Colour	Certifications*	Temperature resistance °C		Solvent resistance	Peel strength (N/cm)	Relative adhesion	
					Long term (days, weeks)	Short term (minutes, hours)			Metals Glass MSE Plastics	Coated & Painted Surfaces
3M VHB Very Conformable										
The conformability of the 3M VHB allows a more complete bond contact area when bonding rigid or irregular materials. These products offer excellent adhesion to the broadest range of substrates. The modified acrylic adhesive is especially developed for powder coated paints. (In many applications, the use of a primer is not necessary on most surfaces.)	5925	0.6	●	UL746C	+120	+150	high	30	high	high
	5952	1.1	●	UL746C	+120	+150	high	38	high	high
	5962	1.6	●	UL746C	+120	+150	high	38	high	high
3M VHB Conformable										
The conformability of the 3M VHB allows a more complete bond contact area when bonding rigid or irregular materials. These products offer excellent adhesion to a broad range of substrates, including plasticised vinyl.	4926	0.4	●	UL746C	+93	+150	high	24	high	medium
	4936	0.6	●	UL746C	+93	+150	high	30	high	medium
	4941	1.1	●	UL746C	+93	+150	high	38	high	medium
	4956	1.6	●	UL746C	+93	+150	high	38	high	medium
	4991	2.3	●	UL746C	+93	+120	high	38	high	medium
	4919	0.6	●	UL746C	+93	+150	high	30	high	medium
	4947	1.1	●	UL746C	+93	+150	high	38	high	medium
3M VHB Tapes For Special Applications										
3M VHB Flame retardant:										
Black. Closed-cell acrylic foam carrier. Highly conformable. Excellent adhesion to painted and powder-coated surfaces. Flame retardant.	5958FR	1.0	●	FAR 25.853	+93	+150	high	35	high	high
3M VHB for high temperatures:										
Dark grey. Closed-cell acrylic foam carrier. Resistant to high temperatures and powder-coating cycles.	4646	0.6	●	UL746C	+150	+232	high	25	high	low
	4611	1.1	●	UL746C	+150	+232	high	31	high	low
	4655	1.6	●	UL746C	+150	+232	high	31	high	low
White. Closed-cell acrylic foam carrier. Resistant to high temperatures and powder-coating cycles.	4613	1.1	○		+120	+150	high	32	high	low
3M VHB for low temperatures:										
Grey. Closed-cell acrylic foam carrier. Conformable. Can be applied at low temperatures (5 °C)	4943	1.1	●		+93	+150	high	44	high	medium
	4957	1.6	●		+93	+150	high	44	high	medium
3M VHB Clear:										
Transparent. Solid acrylic adhesive. Ideal for bonding transparent materials such as glass, polycarbonate and plastics.	4905	0.5	●	UL746C	+93	+150	high	21	high	medium
	4910	1.0	●	UL746C	+93	+150	high	26	high	medium
	4915	1.6	●		+93	+150	high	26	high	medium
	4918	2.0	●		+93	+93	high	26	high	medium
3M VHB for low energy surfaces:										
White. Closed-cell acrylic foam carrier. Good adhesion to polyethylene and polypropylene.	4932	0.6	○		+71	+93	high	35	high	high
	4952	1.1	○		+71	+93	high	44	high	high
3M VHB for high energy surfaces:										
White. Closed-cell acrylic foam carrier. Rigid. Excellent shear performance.	4920	0.4	○	UL746C	+93	+150	high	26	high	low
	4930	0.6	○	UL746C	+93	+150	high	35	high	low
	4950	1.1	○	UL746C	+93	+150	high	44	high	low
	4912	2.0	○		+150	+190	high	35	high	low
	4945	1.1	○	UL746C	+93	+150	high	44	high	low
	4949	1.1	○		+93	+150	high	44	high	low
3M VHB RP.										
Close-cell acrylic foam carrier. Conformable bonding for glass, metal, some plastics, composites, sealed wood.	RP25	0.6	●		+93	+120	high	30	high	medium
	RP45	1.1	●		+93	+120	high	35	high	medium
	RP62	1.6	●		+93	+120	high	35	high	medium

* A current list of UL certified 3M VHB Tapes can be found at www.ul.com (select certifications, search file MH17478)

Important notice: The information contained in this brochure is based on tests and data which 3M believes to be reliable, but the accuracy or completeness of such statements and information is not guaranteed. The user is responsible for determining whether a specific 3M VHB tape is suitable for the purpose intended and for the user's method of application. All questions of liability relating to 3M VHB tapes are governed by our terms of sale subject, where applicable to prevailing.

Industrial Adhesives and Tapes Division

3M United Kingdom plc
3M Centre, Cain Road
Bracknell, Berkshire RG12 8HT
Tel: 0870 60 800 60
www.3M.co.uk/industrial

3M Ireland Limited
The Iveagh Building
The Park, Carrickmines
Dublin 18
Tel: 1 800 320 500

Please recycle. Printed in the UK.
© 3M 2016. 3M and VHB are
trademarks of 3M Company.
All rights reserved. J323612 | CJ1198a

